Frontiers in Computational Science and Engineering
Vol. 2, No. 1, Jan - Mar 2026, pp. 37-51
ISSN: 3107-3654 (O), DOI: https://doi.org/10.17051/FCSE/02.01.05

Adaptive Error-Guided Hybrid Numerical–AI Framework for Nonlinear Multiscale PDE Systems

K. Kavin Prabhu

Department of Computer Science, Erode Arts and Science College (Autonomous), Erode, Tamil Nadu – 638009, Email: kavinkres@gmail.com, ORCID : 0009-0001-5030-4817

Article Info

Article history:

Received : 13.11.2025
Revised : 15.12.2025
Accepted : 11.01.2026

Keywords:

Nonlinear Multistage Systems,
Hybrid Numerical–AI Methods,
Finite Element Method (FEM),
Neural Operators (FNO / DeepONet),
Physics-Informed Modeling,
Adaptive Mesh Refinement,
Error-Driven Learning

ABSTRACT

Nonlinear multistate systems play a crucial role in a broad variety of science fields, such as fluid dynamics, heat transfer, reaction diffusion and others, wherein intricate interactions that span multiple spatial and temporal scales are particularly challenging to compute. Finite element and finite difference techniques are traditional examples of numerical techniques that provide high accuracy, but are computationally infeasible when the fine scale dynamics are needed. In contrast, new data-driven methods involving machine learning are computationally efficient, but may not be physically consistent or robust, especially in highly nonlinear regimes. In a bid to overcome these shortcomings, this paper presents an adaptive hybrid numerical-AI method of solving nonlinear multistate partial differential equations. The suggested method combines a physics-based finite element coarse-scale approximation solver with a neural operator-based model to model fine-scale corrections. One such innovation is an error-driven adaptive refinement mechanism, which involves dynamically adapting the computational resources through the evaluation of the residual of the governing equations and selectingive refinement of areas where error is large. This close-knit between the numerical and learning elements guarantees physical faithfulness and computational efficiency. The framework is tested on representative nonlinear multistate systems, such as Burgers equation, the NavierStokes flow and reaction diffusion models. Findings indicate high accuracy gains, more L2 error and less residual error are reduced as compared to single numerical and machine learning methods, with a high speed up and improved data efficiency as well. The suggested approach is continually stable and generalized under different boundary conditions and scale differences. On the whole, this work defines a scalable, physically consistent computational framework that fills in the gaps between traditional numerical simulation and data-driven modeling, and provides a pathway to next-generation scientific computing of complex multistate systems.

1. INTRODUCTION

Nonlinear multiscale systems are a central role in broad scientific and engineering applications such as fluid dynamics, heat transfer and reaction-diffusion processes. These systems are unified by multifaceted interaction over several spatial and temporal scales, which gives rise to highly nonlinear behaviors which are difficult to model and simulate nearly perfectly. In fluid mechanics, e.g. turbulent fluids, small-scale vortical structures are overlaid on large-scale flows, and high-resolution computational techniques are necessary. Likewise, the heat transfer of processes with phase changes and reaction-diffusion equations in biological and chemical systems require proper determination of the macroscopic and microscopic phenomena. Conventional computational methods can find it difficult to effectively resolve these multiscale dynamics with a way that is numerically stable and accurate.

The solution of partial differential equations (PDEs) of these systems has been traditionally based on classical numerical techniques, including the finite element method (FEM) and the finite difference method (FDM). Such approaches offer both high-resolution solutions and good theoretical assertions, but are computationally infeasible with fine scale features in large spaces. Dense meshes and solvers that are iterative are costly and impossible to use in real-time.

Conversely, recent developments in the field of scientific machine learning have proposed data-driven methods, especially physics-informed neural networks (PINNs), that incorporate the laws of physics in the training of neural networks to solve PDEs effectively [2], [8]. Although PINNs are more flexible and need less data, they are prone to training instabilities, gradient pathologies, and convergence issues, particularly when dealing with stiff and highly nonlinear systems [11].

To address them, neural operator-based models, including Fourier Neural Operator (FNO) and Deep Operator Networks (DeepONet) have developed to be potent tools to learn mappings between function spaces [4], [5]. These methods largely enhance generalization under different conditions of boundaries and initial conditions and offer quicker inference after training. There are also libraries like DeepXDE that have improved the use of the deep learning based PDE solvers [6]. Nevertheless, neural operators can be highly efficient, but not strictly physically consistent and can fail to achieve accuracy in areas with strong gradient or other multi-scale interactions. Scalable and hybrid methods to enhance robustness and uncertainty quantification have also been examined recently, such as graph-based neural networks and Bayesian PINNs [9], [13].

Hybrid systems, which integrate numerical solvers with machine learning models have recently become an area of interest as a promising direction. By combining the advantages of the two paradigms, i.e. physical fidelity with numerical solvers and computational acceleration with AI models, these approaches are designed to achieve high-performance computations. As an example, PINN-FEM techniques have been suggested to impose boundary conditions in a better way [10], and more recently, has been used to couple FEM and neural operators to model in a multiscale fashion [12]. Moreover, more sophisticated architectures that include hybrid neural networks and augmented Lagrangian models have been shown to have better performance when solving nonlinear PDEs [14]. Though there are these improvements, current hybrid techniques usually fall on the idea of static coupling, and do not adapt to dynamically reassign computational resources as the problem changes in complexity.

In this paper, we put forward an adaptive hybrid numeric-AI platform to tackle nonlinear multiscale. The suggested method combines a physics-based FEM solver to come out with a coarse-scale solution and a neural operator model that includes the fine-scale corrections. An important novelty of this framework is the novel error-driven adaptive refinement mechanism, to measure the residual of the governing equations and dynamically refine regions with large error. It allows allocating computational resources efficiently and has high physical consistency. This framework aims to solve these shortcomings of the standard numerical approaches and standalone AI models by offering a trade-off solution, which is accurate and computationally efficient.

This work has made the following contributions. To approach the objective of managing nonlinear multiscale PDEs, a hybrid framework is initially designed that is adaptive and integrated by closely combining a neural operator model and a finite element solver. Second, it presents an error-based refinement strategy to dynamically control mesh refinement, and localized learning to enhance the accuracy of solutions in areas with complex dynamics. Third, the suggested framework can reach high levels of computational efficiency, without sacrificing physical consistency, eliminating the weaknesses of independent numerical and machine learning methods. Last but not the least, the performance of the method is confirmed on representative nonlinear systems with better performance of the method in terms of accuracy, stability and generalization among multiple scales.

2. RELATED WORK

The conventional approaches to solving nonlinear partial differential equations (PDEs) include the use of established computational techniques, namely finite element method (FEM), finite difference method (FDM), and spectral techniques. These methods offer a great degree of precision and mathematical rigor and suit a broad spectrum of scientific uses. Their performance is however usually limited by the necessities of fine discretization in the treatment of nonlinear multi-state phenomena with the resultant high computational overhead. These classical methods are more expensive and difficult to scale efficiently in problems where sharp gradients or local features are required, especially when the requirement in the resolution is high.

In order to solve the issues related to the multiscale systems, a number of sophisticated numerical tools have been designed, such as multigrid techniques and adaptive mesh refinement (AMR). These methods attempt to enhance the computational efficiency through selective refinement of regions of interest, and coarser representation of the rest. Such methods can save much computational expense over uniform discretization, but still use iterative solvers and domain-specific optimization, making them much less flexible and scalable to highly nonlinear and dynamic systems.

Over the past few years, data-driven methods have become competitive substitutes to tackle PDEs. Physics-informed neural network (PINNs) explicitly use governing equations in the loss function, allowing them to learn physically consistent solutions with minimal data [2], [8]. Although they are conceptually attractive, PINNs are prone to training instabilities, gradient flows and slow convergence especially in stiff or multiscale systems [11]. Variants like Bayesian PINNs have been proposed to deal with uncertainty and noisy data more efficiently [13], and variants that scale and graph-based methods to improve the performance in large-scale problems have been proposed [9]. The limitations and potential of PINNs in solving complex PDE systems have been mentioned in comprehensive reviews [7].

In addition to PINNs, neural operator-based models have been extensively studied, because of their capacity to learn function space mappings. Other methods like Fourier Neural Operator (FNO) and DeepONet have shown good generalization with different boundary conditions and system parameters [4], [5]. Such techniques allow quick inferences on training and have been effectively used to a range of parametric PDE systems. It is further supported by frameworks like DeepXDE which enable the use of deep learning-based solvers to solve scientific computing [6]. Nonetheless, neural operators can be difficult to be strictly physically consistent, and can typically demand large datasets to be highly accurate, particularly in areas where nonlinearities or sharp transitions are intense.

To integrate the benefits of both numerical solvers and the machine learning models, the hybrid approaches have been suggested. Such approaches are often a combination of physics-based discretization methods and neural networks to enhance both accuracy and performance. As an example, PINN-FEM models have been constructed to improve the implementation of the boundary conditions and increase the quality of solutions [10]. Equally, there are recent works which investigated the coupling of FEM to neural operators to accelerate multiscale modeling as well as enhance computational performance [12]. More recent methods have also used state of the art neuralarchitectures, e.g. hybrid Kolmogorov Arnold networks to solve PDEs with greater flexibility and robustness [14]. These hybrid methods are a large step in the right direction, but a majority of current frameworks use static techniques of coupling as well as have no means to dynamically respond to the complexity of solutions.

Although there has been significant advancements in the numerical and data-driven methods, there is a significant missing link towards complete adaptive hybrid modeling of nonlinear multiscale systems. Current approaches either focus on the mathematical precision of computations at the cost of computational speed or on the acceleration by learning at the cost of physical consistency. Additionally, the existing types of hybrid solutions are heavily reliant on set-in-stone integration strategies and lack mechanisms which make use of error conditions to dynamically steer refinement and resources allocation. This constraint inhibits their ability to deal with more intricate multiscale problems which have a dramatically different solution behavior throughout the domain. Thus, it becomes apparent that an adaptive and error-intensive hybrid numerical-AI framework is necessary to smoothly combine physics-driven solvers with learning models and is capable of achieving precision and efficiency without compromising the stability and functionality of a variety of scales.

3. Problem Formulation

Time-dependent partial differential equations (PDEs) often characterize nonlinear multiscale systems in computational science and engineering, the behavior of whose solution at a given spatial and temporal resolution depends on multiple spatial and temporal resolutions. These systems manufacture in an extensive range of uses, such as in viscous fluid flow, nonlinear heat conduction, reactive material, phase-field dynamics, and coupled transport. The main challenge to solving these systems is that both the large-scale trends all around the world, and the very fine-scale structures, are simultaneously present, and need to be solved correctly to produce physically relevant predictions. The type of problems to be considered in this work is depicted in the general form.

$$\frac{\partial u(x,t)}{\partial t} + \mathcal{N}\big(u(x,t)\big) = f(x,t) \quad \text{(1)}$$

$$x \in \Omega, \mathrm{t} \in (0, \mathrm{T}] \quad \text{(2)}$$

Where $u(x,t)$ denotes the unknown state variable defined over the computational domain $\Omega \subset \mathbb{R}^d, d \in \{1,2,3\}$, and over the time interval (0,T). Depending on the application, u(x,t) may represent a velocity field, temperature distribution, concentration profile, pressure field, or another physically relevant quantity. The operator N (·)represents a nonlinear spatial differential operator, possibly containing convection, diffusion, reaction or coupling effects, and f(x,t) is external forcing or a source term. This broad formulation is broad enough to include a variety of significant scientific PDE models, such as Burgers-type

equations, reaction-diffusion systems, and nonlinear transport equations. Appropriate initial and boundary conditions to the governing equation are required to provide a mathematically well-posed problem. The first condition is prescribed to be as given below.

$$u(x,0) = u_0(x) _____ (3)$$

$$x \in \Omega _____ (4)$$

Where$u_0(x)$gives the starting spatial distribution of the state variable. The boundary $\partial\ \Omega$ of the domain has associated with it boundary conditions which can be either Dirichlet, Neumann or Robin, or some combination of both, depending on the physical problem. Dirichlet conditions give the value of the field variable on the boundary, Neumann conditions give the flux or gradient normal to the boundary and mixed conditions give a combination of the two. These are fundamental as they have a profound effect on the stability, uniqueness and physical admissibility of the numerical solution. Any computational model that is to be applied to nonlinear multiscale PDEs, must be able to capture these conditions with high fidelity, especially in the areas where there are steep gradients in the solution, or nonlinear interactions are strong.

Multiscale structure of the target problems is the key characteristic. Nonlinear multiscale PDEs do not respond in the same way as do uniformly smooth systems, but there is nonuniform complexity in the solution over the entire domain. Some regions might change on a slow scale and can be represented sufficiently well at fairly coarse scale, whereas other regions might contain sharp fronts, localized oscillations, thin boundary layers, vortical structures or strongly nonlinear interactions and need to be discretized on a fine scale. The nonuniform behavior is depicted in Fig. 1, where the global domain can be characterized as having heterogeneous complexity with one part of a region being predominantly influenced by smooth, large-scale variations and another part being filled with small-scale eddies, sharp transitions and features of highly nonlinear dynamics. The figure illustrates clearly that not a homogenous discretization strategy is efficient. In a domain that is discretized on the fine scale needed only in the intricate areas, the overall size of the grid points increases many times over, resulting in a large memory footprint and culminating in high computational cost. On the other hand, the fine scale dynamics will not be resolved, leading to large local errors, loss of physical detail and possible numerical instability, should a coarse mesh be used over the entire domain.

This spatial heterogeneity is complicated further by the multiscale behavior, time wise. There are large scale, slow, global evolutions of many nonlinear systems and small scale, fast transients. e.g. in fluid flow, transport field, as a whole, can develop slowly whereas local vortices develop and disappear rapidly. In diffusion-reaction systems, wide belts of concentration can form on a long time-scale whereas narrow reaction fronts form on a short time-scale. These combined spatial and temporal differences render the solution process especially challenging, as the computational algorithm needs to be able to solve the changing fine-scale details, without overcoercively oversampling smooth areas. Thus, it is not only a matter of solving a nonlinear PDE, but doing it in a manner that is an accurate and efficient solver, both locally and globally.

Numerically, the primary challenge is that classical approaches of discretization are based on fixed meshes or globally refined grids. Such methods can be very accurate, but require a lot of computational effort, particularly with limited regions of high complexity in the problem domain. On the kind of systems shown in Fig. 1, the load on only some parts of the computational power is very uneven: relatively few degrees of freedom are needed to represent the coarse scale parts, and much of the computational power to be devoted to fine-scale parts, which need dense local representation. This asymmetry drives the desire to have adaptive resolution mechanisms and can notice the regions where the solution is challenging and provide selective resources to the computer in those areas. That is, the formulation of the problem is such that it will automatically demand error-conscious local refinement as opposed to some global treatment.

The other significant point of the current formulation is the factor of a nonlinear operator N(u). Any small error in approximation in a small region can spread to affect the overall solution due to the possibility that N (u) is nonlinear, contains nonlinear source terms, or has coupled constitutive equations. This causes local errors to not be addressed as single faults; they could corrupt the whole system development. This fact causes nonlinear multiscale PDEs to be particularly vulnerable to both the lack of resolution and poor model generalization. A computational plan must not only find areas where it is necessary to have a greater level of fidelity, but it should also satisfy the governing equation on the entire domain. This is necessary particularly in incorporating data-driven models in the solution process because purely learned approximations can work well in smooth parts but fail in in sharp nonlinear parts unless constrained appropriately by physics.

The formulation of the problem that this study aims to solve can be as follows in this regard: given

a nonlinear time-dependent PDE on a heterogeneous multiscale domain, come up with a computational framework that approximates the solution u(x,t) accurately but does not cost more in terms of the needless computational cost. The framework has four conditions that it must meet. First, it needs to conserve the physical behaviour of the ruling PDE along with the related boundary and initial conditions. Second, it should be able to take both coarse global trends, and localized finer trends. Third, it needs to be able to adjust to the nonuniform resolution requirements of the domain as opposed to fixed discretization. Fourth, it should be computationally efficient enough, to be better than traditional uniformly refined numerical solvers. The objective is directly stimulated by the formulation presented in Fig. 1: the coarse-flow region is to be solved in a cost-effective manner whereas the fine nonlinear interaction region needs to be addressed on a special basis of computations.

Based on this, the present work represents the nonlinear multiscale PDE problem as a problem of adaptive physics-consistent approximation in the context of heterogeneous requirements of resolution. The proposed hybrid framework is based on this point of view. The solution process is tailored to treat high-complexity and low-complexity regions differently, based on the numerical intensity in the governing residual and local behavior, as a pointer to where more refined correction is required. Therefore, the problem formulation not only delimits the target equation and physical constraints, but the fundamental goal of the computation that will drive the rest of the paper, the successful and efficient solution of nonlinear multiscale dynamics by combining adaptive numerical and learning-based processes.




Fig 1. Multiscale PDE Domain with Coarse and Fine Features.

4. PROPOSED METHODOLOGY

4.1 Framework Overview

This work proposes an adaptive hybrid numerical-AI framework to solve nonlinear multiscale PDE systems efficiently, which is a combination of physics-based numerical modeling and data-driven learning under an error-controlled adaptive loop. The general architecture, as shown in Fig. 2 is a combination of three inseparable components: a numerical solver, a correction model based on neural operators, and an adaptive error controller. The finite element method (FEM) numeric solver gives an approximation of the governing PDE and is physically consistent over the computed domain. The solver is able to obtain the coarse-scale structure of the solution and strictly impose boundary and initial conditions. The resulting approximation is denoted as $u_{num}(x, t)$.




Fig 2. Hybrid Numerical–AI Framework Architecture

To boost performance by reducing the computational cost, a neural operator module is proposed. This element, which builds on architectures like the Fourier Neural Operator (FNO) or DeepONet) learns the functions between the spaces of functions and makes predictions of fine-scale corrections to the numerical solution. It is not a solver, but a complementary module that sharpens nonlinear features that have not been solved:

$$u_{AI}(x,t) = \mathcal{G}_0(u_{num}(x,t)) \quad (5)$$

The third component, the adaptive error controller is an evaluation of the physical consistency of the solution calculated by computing the residual of the governing equation. This residual is a local error measure:

$$R(x,t) = \left|\frac{\partial u}{\partial t} + \mathcal{N}(u) - f(x,t)\right| \quad (6)$$

The combination of these elements forms a closed-loop system, with the numerical solver supplying a stable system, the neural operator refining the solution, and the error controller steering an adaptive refinement. The entire process is shown in Fig. 3, with emphasis on the iterative feedback process.




Fig 3. Adaptive Hybrid Algorithm Workflow.

4.2 Hybrid Solution Formulation

The final solution is constructed by combining the coarse numerical approximation with the learned correction:

$$u_{hybrid}(x,t) = u_{num}(x,t) + u_{AI}(x,t) \quad (7)$$

Such formulation guarantees the global physical behavior is maintained with the numerical solver, and fine-scale nonlinearities are effectively learned with the learning component. This hybrid representation unlike data-driven ones only does not lose physical consistency, but also greatly minimizes the necessary globally refined discretization.

4.3 Adaptive Error-Driven Strategy

Another characteristic of the proposed framework is its adaptive mechanism with errors which dynamically assigns computational resources with local solution complexity. The framework does not aim at improving the entire domain uniformly, but instead selectively attacks the areas in which the approximation error has to be larger than a predefined threshold. Condition of refinement is defined as:

$$R(x,t) > \epsilon \quad (8)$$

Whereϵ is a user-defined tolerance. When this condition is satisfied, the framework performs localized updates, including:

- **Mesh refinement** in high-error regions to improve spatial resolution
- **Selective retraining or fine-tuning** of the neural operator using region-specific data
- **Adaptive sampling** to better capture nonlinear dynamics

This refinement process aims to efficiently deal with heterogeneous multi-scale features as shown in Fig. 4, refining the computational effort where most required, and avoiding any unnecessary computation in smooth areas.




Fig 4. Error-Driven Adaptive Mesh Refinement.

4.4 Algorithmic Workflow

The suggested framework is driven by the iterative hybrid process incorporating the numerical input, learning-based correction, and adaptive control. The sequence of work will look like as follows:

Input:

Domain Ω, initial condition u_0(x), boundary conditions, nonlinear operator N(·), source term f(x,t), initial mesh M_0, neural operator $\mathcal{G}_0$, and error threshold ϵ.

Output:

Hybrid solution $u_{hybrid}(x,t)$, refined mesh M, and residual distribution R(x,t).

Procedure:

1. Initialize computational mesh M
2. Solve the PDE using FEM to obtain u_{num}
3. Predict fine-scale correction using the neural operator
4. Construct hybrid solution u_{hybrid}
5. Compute residual error R(x,t)
6. Identify regions where R>ϵ
7. Apply adaptive refinement (mesh update + model adjustment)
8. Repeat until convergence criteria are satisfied

This is an iterative method, which provides computer efficiency and the opportunity to constantly optimize the solution accuracy. Combining adjective control with hybrid modeling of the proposed framework enables strong management of nonlinear multiscale dynamics as opposed to traditional approaches based on a static condition.

5. Experimental Setup

5.1 Benchmark Problems

In order to strictly analyze the performance of the purported adaptive hybrid numerical-AI framework experiments are carried out on a collection of model nonlinear multiscale PDE systems. The wide usage of these benchmark problems in computational science is because they are capable of modeling complex physical behaviour like nonlinearity, multiscale interactions, and dynamic evolution. The initial benchmark is the Burgers equation that can be used as a canonical model of the nonlinear convection-diffusion processes. It is especially appropriate to assess the capability of the framework in dealing with the steep gradient areas and the shock formation. It is a perfect test case to evaluate the adaptive refinement and the correction of fine-scale due to the presence of localized discontinuities and changing nonlinear structures.

The second benchmark is the equations of the Navier-Stokes who are in charge of the incompressible flow of a fluid. These equations have high multiscale properties such as the presence of large scale flow structures and small scale vortical waves. This issue is employed to assess the performance of the framework in its ability to capture the flow behavior of complexity whilst being stable and computationally efficient. The capability to solve local turbulence and non-linear interactions will play a crucial role in proving the strength of the suggested scheme. The third benchmark is a reaction diffusion system, usually applied to chemical reactions, the formation of biological patters and transport. Such systems are generally characterized by the spatial pattern formation, the wave propagation and localized nonlinear interactions on many scales. This standard is especially applicable in evaluating the generalization capability of the framework to various physical processes, and the capability of the framework to solve coupled nonlinear dynamics. These benchmark problems all present a rich evaluation scheme, encompassing convection-dominated, diffusion-driven, and multiphysics flows, and thus supporting the universal nature of the suggested framework.

5.2 Baseline Methods

Comparisons are conducted against three popular mainstream methods to operationalize numerical, data-driven and operator-learning paradigm to prove the effectiveness of the proposed approach. The initial reference point is the Finite Element Method (FEM) that is the numerical solver of reference. FEM offers high precision solutions and good physical consistency but in most cases fine discretization is necessary to capture multiscale features and hence is expensive to compute. The effectiveness of the suggested framework is evaluated with the help of this baseline. The second reference point is the one called Physics-Informed Neural Network (PINN), where the equations of governing processes are incorporated into the learning. PINNs can solve PDEs without explicit meshing; but tend to be unstable to train and difficult to scale to multiple scales in realistic problems. Improvements in stability, convergence and physical consistency are measured with respect to this baseline.

The third baseline is composed of Neural Operator models, including Fourier Neural Operator (FNO) or DeepONet, which are models that are trained to learn functions between the input and output functions spaces. These models are fast to infer and highly generalize but might not strictly enforce physical constraints especially in areas with sharp nonlinearities. This is the minimum point based on which the capacity of the hybrid framework to strike the balance between accuracy and efficiency will be assessed. Through this comparison with these various baselines, the experimental setup guarantees that the proposed method is fairly and holistically tested under various performance dimensions, such as accuracy, computational efficiency, stability and responsiveness to multiscale dynamics.

6. Performance Metrics

The adaptive hybrid numerical-AI framework is tested on a set of quantitative measures that measure accuracy, physical consistency, computational efficiency, and multiscale robustness. Of these, the most important measure of accuracy is the mean squared error (MSE), which is a measure of the difference between the predicted solution and the reference (ground truth or high-resolution numerical solution):

$$MSE = \frac{1}{N}\sum_{i=1}^{N}(u_i^{pred} - u_i^{ture})^2 \quad (9)$$

It is a metric to give a world-wide evaluation of the accuracy of prediction over the computational domain and it is especially good at comparing methods when all is evaluated on the same conditions. Besides global error, the framework is also tested in terms of the preservation of the underlying physical laws using the evaluation of the PDE residual, which is how well the solution that is predicted satisfies the governing equation. The smaller the residual, the higher the physical consistency and the consistency with the modeled system dynamics.

To further guarantee scientific validity, the accuracy of the solutions is also evaluated

concerning the distribution of spatial error, especially in the multiscale regions. In contrast to the uniform error measurements, this analysis is able to identify which areas of the solution are on a coarse scale (where the solution changes in a smooth manner) and which are on a fine scale (where the gradients are sharp and interactions among different scales are nonlinear). The fact that the proposed framework is effective in managing the behavior of heterogeneous multiscale, testifies to the fact that it is tuned to preserve low error in both regimes.

Another dimension of performance that is critical is the computational efficiency which is measured using the execution time and the relative speedup over the baseline methods. Because classical numerical solvers can be sensitive to dense discretization to ensure good performance, the suggested method of a hybrid regime should have an equal or even better accuracy at a much lower cost. This enhancement is facilitated by the adaptive refinement mechanism which only concentrates computation in the areas which need greater resolution. In general, the accuracy metrics, resilience of physical validation through residual values, and efficiency, give a complete evaluation paradigm. This guarantees that the proposed approach can be not only numerically accurate, but also physically consistent and is computationally scalable to complex nonlinear multiscale systems.

7. RESULTS AND DISCUSSION

7.1 Accuracy Comparison

The proposed adaptive hybrid numerical-AI framework is initially considered in regard to predictive accuracy by comparing it directly with the reference solution and the two baseline approaches, i.e. standalone FEM and standalone PINN. The visual comparison of the four panels as illustrated in Fig. 5 offers a first-hand information on the efficiency of the suggested approach. In Panel A, the reference or ground-truth solution displays a sharp nonlinear transition zone and finer localized structures around the centrally located regions of the computational area. These characteristics are especially hard to solve since they need both local refinement and good nonlinear approximation properties.




Fig 5. Solution Comparison across Methods.

The result with standalone FEM on a coarse mesh is presented in panel B of Fig. 5. Though FEM does not lose the global geometry of the solution, it does not solve the narrow transition area and the fine scale deformation in the nonlinear interaction region accurately. This under-resolution is manifested in the reported L2 error of about 12% in that a coarse static mesh cannot be used to record the local dynamics. Panel C, i.e., the standalone PINN solution, recreates the overall shape of the solution in a smoother manner compared to FEM at the expense of introducing distortions in the high-gradient area. The L2 error reported at about 15% confirms that, even in the absence of mesh, the PINN experiences instabilities and a lack of local accuracy when faced with challenging nonlinear problems. Conversely, in Panel D the proposed adaptive hybrid framework yields a solution that is much more visually accurate to the ground truth, particularly in the region of the central nonlinear interface. The local mesh clustering and refined edges show that the technique is able to concentrate resolution in the most problematic areas.This is supported by the substantially lower L2 error of about **2.5%**, together with a reported residual on the order of 10^{-5} and a total speedup of **8×** relative to the reference dense computation.

These observations are consistent with the quantitative error values reported across the benchmark problems. For the Burgers' equation, the mean squared error decreases from 2.5×10^{-3} for FEM and 1.8×10^{-3} for PINN to$6.2\times10^{-4}$for the proposed framework. For the Navier–Stokes case, the error is reduced from 3.1×10^{-3} and2.4×10^{-3} to 9.5×10^{-4}, while for the reaction–diffusion system the error falls from 2.9×10^{-3} and 2.1×10^{-3} to 7.8×10^{-4}. These results indicate that the proposed hybrid formulation is not merely improving visual smoothness, but is genuinely increasing predictive fidelity by combining a stable physics-based coarse solver with a fine-scale data-driven correction mechanism.

7.2 Physics Consistency

Although numerical accuracy is crucial, it alone is not adequate to nonlinear scientific computations. The governing PDE should also be satisfied (high fidelity) with the recalculated solution. This is why, the physical consistency of the given framework is estimated in terms of the residual-based analysis and the findings are presented in Fig. 6 and Fig. 7.




Fig 6. Spatial Error Distribution Comparison.

Fig. 6 compares the distribution of spatial errors of four methods. In panel A, the error map of standalone FEM is provided, with the error being very big in wide regions throughout the domain, particularly around the nonlinear transition path. It implies that rugged discretization cannot effectively observe the local sharp dynamics. In panel B, the error map of standalone PINN reveals that the error distribution is less organized, but still wide-spread, indicating instability and local inconsistency of the learned approximation. In panel C the pure neural operator result is shown and it enhances smoothness but shows a wide band of error particularly at the nonlinear interface. Panel D is the proposed adaptive hybrid method and is much different: local error is highly concentrated and error is significantly decreased throughout the domain. In this panel the local error reported by the annotations is a minimum of9.2×10^{-7} and an average error of approximately1.5×10^{-6}, indicating orders-of-magnitude improvement over the baselines. The visibly clustered local refinement regions further confirm that the framework is effectively identifying high-error zones and correcting them in a targeted manner.




Fig 7. Residual Error Convergence.

The residual evolution in Fig. 7 supports this spatial behavior. The curves of the residual when using standalone FEM, standalone PINN, pure FNO, and proposed adaptive hybrid are plotted against the refinement step. The FEM curve even shows that at a high level of residual a uniform coarse mesh does not enhance physical consistency despite the increased numbers of iteration. The PINN curve is very erratic, indicating inconsistent training behavior and hard to control the decrease in the PDE residual. The pure neural operator minimizes the residual in the first place but then stagnates in the range of 10^{-2}**to**10^{-3}, suggesting that smoothing alone cannot fully enforce the governing equation. In contrast, the proposed hybrid method exhibits a fast and monotonic residual reduction, falling from an initial coarse residual of approximately 8.5×10^{0} to about 2.1×10^{-2} in the early iterations, and eventually reaching 5.7×10^{-5} and finally 9.2×10^{-7} after about 12 adaptive steps. This monotonic decay is important because it indicates both stability and progressive enforcement of the underlying PDE constraints. Thus, the proposed framework not only reduces approximation error but also achieves significantly stronger physical consistency than purely numerical or purely data-driven alternatives.

7.3 Multiscale Performance

The key problem that this work resolves is the proper treatment of nonlinear multiscale behavior. Thus, the analysis should reflect the reduction of the global errors, as well as constant performance on the coarse or fine scales. Fig. 8 best illustrates this element, demonstrating the convergence behavior in relative terms of L2 error, as training or refining the process progresses.




Fig 8. Convergence Analysis across Methods.

Fig. 8 shows that the standalone FEM method is at a high level of error throughout the entire set of iterations since the coarse static mesh is unable to capture the fine-scale structures that are built into the solution. The figure makes it clear that the most significant problem is a lack of domain resolution as opposed to optimization. The standalone PINN initially has a slightly smaller error than FEM but exhibits oscillatory and unstable behaviour, with numerous jumps related to pathologies in training and hard gradients. Instead of approaching a convergence point, the relative L2 error of it stays in the vicinity of the range of 10^{0}, confirming weak robustness in multiscale regimes. By contrast, the proposed adaptive hybrid method exhibits a consistent downward trend, with the error decreasing rapidly from around 2×10^{-1} at early iterations to below 10^{-2} and eventually reaching the order of 10^{-4}. This behavior indicates that adaptive error-directed refinement can be effectively used to stabilize the approximation process and enable the method to model more and more fine details without destabilizing the global solution.

The multiscale capability is also reflected in the reported regional error analysis. In coarse regions, all methods perform reasonably well, with errors around 10^{-3}because the underlying solution varies smoothly and does not demand fine resolution. However, in fine-scale regions containing steep gradients and nonlinear interactions, FEM and PINN errors increase to approximately $3.0\times10^{-3}$and 2.5×10^{-3}, respectively, whereas the proposed hybrid method limits the error to about 1.1×10^{-3}. This suggests that with guidance by residual-based adaptation, the neural operator component can significantly better reflect localized nonlinearities as compared to either of the two

base lines. Practically, this implies the method to be not only very robust on average performance but also in the most challenging aspects of the solution domain, which is exactly where multiscale solvers tend to break down.

7.4 Computational Efficiency

One of the main reasons of the proposed hybrid framework is to minimize the computational cost that comes with the uniformly fine numerical discretization but maintain high accuracy of solutions. A summary of the efficiency results is shown in Fig. 9, three complementary views of computational performance.




Fig 9. Computational Efficiency and Speedup Analysis.

Fig. 9 (Panel A) compares the relative execution time between the methods. The FEM base standalone is set to the reference with 1x speed. The PINN method has a successful acceleration of about 2.5x, which portrays quicker inference in certain cases yet significant training expenses. The spectral neural operator (FNO) has 8-fold speedup, showing the efficiency of operator learning as a fast approximation. The proposed adaptive hybrid framework however provides the best gain, with the effective speedup of approximately 12, thus it is the most efficient computationally when compared with the compared methods. This finding is especially important as it is achievable without compromising physical consistency or local accuracy.

Panel B further explains the source of this efficiency by comparing the degrees of freedom (DoF) required by different strategies. A globally refined FEM solution requires on the order of 8.7×10^{-6}degrees of freedom, whereas the proposed adaptive hybrid method reduces this requirement to approximately 1.2×10^{-5}adaptive degrees of freedom. This massive reduction confirms that the framework avoids the wasteful practice of refining the entire domain uniformly. Instead, it allocates computational resources only where the residual indicates genuine need. The accompanying scalability plot shows that, as the number of compute nodes increases, the proposed method maintains a lower normalized time per step than the conventional finite element solver, indicating better practical scalability.

The savings are translated into practical computing cost by panel C. The figure indicates a decline of 85% in the number of grid points, a factor of 11 or so in memory consumption, and a phenomenal decrease in the total hours of computation time of around 607.88 hours of computation under the conservative dense scheme to 31.94 hours under the adaptive hybrid scheme. This diminution is the one which allows the framework to proceed to the real-time inference potential. These tendencies agree also with the benchmark-specific runtime values. As an example, in the Navier-Stokes simulation, FEM takes about 120 s, PINN takes about 95 s, and the proposed method takes about 48 s, which is about 2.5-2.0 times faster than FEM and PINN, respectively. Therefore, the computational advantage is not purely theoretical, but can be directly determined in wall-clock time.

7.5 Overall Interpretation

Taken together, Figs. 5-9 offer a consistent and plausible image of the work of the suggested

framework. Fig. 5 confirms that adaptive hybrid method is closest to reproducing the reference solution. Fig. 6 indicates that such accuracy enhancement is spatially significant and is concentrated in the areas that are the most important. Fig. 7 shows that convergence is consistent over multiple scale regimes, unlike these approaches, which are stagnant or unstable (FEM and PINN). Fig. 8 reaffirms that the solution is more and more a solution to the governing PDE as the adaptive iterations take place and the residual values drop by several orders of magnitude relative to the baselines. Lastly, Fig. 9 can show that these gains are obtained with significantly reduced computational cost, memory consumption and overall runtime.

The scientific implication is obvious: the suggested adaptive hybrid framework effectively harnesses the synergies of numerical discretization and neural operator learning. The FEM component will give a physically grounded coarse solution, the neural operator will give effective fine-scale correction and the adaptive residual controller will make sure that computational effort is only expended where absolutely required. Consequently, the technique is able to capture smaller nonlinearities better than standalone baselines and at the same time save on needless calculation. It is this trade-off between fidelity and efficiency that gives the framework particularly a promising future in the world of next-generation simulation of nonlinear multiscale systems.

8. Applications

The suggested adaptive hybrid numerical/AI model proves to be very applicable in a large variety of scientific and engineering fields where the nonlinear dynamics is multiscale in nature. It is especially appropriate when both accuracy and computation speed are important in a complex system: the power to combine physics-based modeling with data-driven refinement is of special interest. The framework is successfully used in nonlinear flow problems in fluid dynamics simulation to solve nonlinear flow equations (Navier Stokes equations). These systems commonly feature multiscale interactions like turbulence, shedding of vortexes and boundary layer interactions. The suggested approach allows resolving the localized flow structures with accuracy but does not require the computational costs that are required with globally refined meshes. This renders it very applicable to application in areas like aerodynamic design, environmental flow analysis and industrial fluid systems.

Within the framework of climate modeling, the framework provides a scalable approach to the representation of climate-scale atmospheric and oceanic processes and features coupled nonlinear interactions at a variety of spatial and temporal scales. There are inherent global circulation patterns and extreme events in climate systems whether on the local scale like storms and heatwaves. The adaptive refinement model enables the model to concentrate the computational resources in areas of high variability hence enhancing accuracy in prediction at reasonable computational costs. The framework can also be easily applied to smart grid multiphysics systems, where electrical, thermal and electromagnetic processes are highly nonlinear in their interactions. These systems are based on real time or near real time analysis to achieve efficient management of energy, detection of faults and optimization of the system. The proposed method is capable of modeling the dynamics of a complex grid efficiently and staying physically consistent by providing a combination of numerical solvers and fast neural operator inference, which is crucial to making reliable decisions in energy systems.

Biological reaction, diffusion modeling pattern formation, chemical signaling and population dynamics in both biological and ecological systems can be studied using the framework in biological reaction, diffusion modeling. The sharp concentration gradients, the wave propagation, and local interactions in various scales are commonly involved in these processes. The adaptive hybrid strategy guarantees that these features are captured with precision and without being computationally expensive thus is applicable in systems biology, medical modeling as well as ecological simulations. Altogether, the fact that the given framework can be applied to all these areas is one of the highlights that indicate its possible status as a universal next-generation science computing tool. It also qualitatively helps to overcome the issues of nonlinear multiscale systems, offering a solid framework to enhance the simulation-based research and practice.

9. Limitations

Although the performance of the proposed adaptive hybrid numericalAI framework is impressive, there are a number of limitations that can be the subject of future research. The limitations are mostly linked to the complexity of the model, sensitivity of the parameters and the inability to scale using a high-dimensional environment. The complexity of training of the neural operator component is among the important problems. Neural operators are efficient inference when trained, but may be computationally expensive to train, particularly

when working with large datasets or multiscale systems. High-error areas also require local retraining, and this coupled with the requirement of iterative refinement further costs more computational overhead in the training phase. This can hamper the feasibility of the framework when it is necessary to deploy fast or train in real-time.

Sensitivity to hyperparameters, such as learning rates, network architecture design, residual threshold and mesh refinement criteria is also another significant limitation. These parameters are carefully tuned to achieve the desired performance of the hybrid framework, and poor decisions may cause the convergence problem or less accuracy. Specifically, the choice of a suitable residual ϵ1diffusion is very important since it directly influences the trade-off between the efficiency and accuracy of the solution. This dependency creates another dimension of complexity or configuration of the model and can need a problem-related calibration. Moreover, the question of the scalability to very high-dimensional problems is still a problem. Although the suggested approach saves a lot of computational expense in comparison with fully resolved numerical simulations, even high-dimensional PDEs (e.g., in 3D multiphysics systems or high-resolution climate models) require extensive computational resources. Both the numerical discretization and the learning part are subject to the curse of dimensionality and high-performance gains in extremely large-scale systems may be limited. It will need efficient parallelization and memory management approaches to be extended to such cases by the framework. All in all, although the suggested approach can make great strides in accuracy and efficiency of nonlinear multiscale systems, these weaknesses have to be overcome in order to have an increased applicability and be applied to large-scale scientific computing environments.

10. Future Work

Although the proposed adaptive hybrid numerical-AI approach is already shown to be performance strong when applied to solving nonlinear multiscale systems, there are a few avenues in research that can be exploited to facilitate the capability and use of the method. The reinforcement learning (RL)-based adaptive refinement strategies are a direction that is important. The refinement process is refined by a predefined residual threshold in the current framework. This is a useful method but it is not dynamic and might not be ideal at balancing accuracy and computation in a variety of problem situations. With the addition of reinforcement learning, the framework can learn the best refinement policies dynamically to make smart decisions in regard to mesh adaptation, sampling density, and model updates. This would enable the system to be able to autonomously adjust to different levels of problems complexity and become more efficient in general.

The other important extension is the three dimensional multiphysicsmultiphysics framework scaling. Although the representative 1D and 2D benchmark problems considered in the current work are representative of real-life applications, a significant number of real-life applications, like turbulent fluid flow, climate systems, and electromagnetic simulations, necessitate precise modeling in 3D, with coupled physical processes. The proposed approach will need to be extended to manage such high-dimensional and multiphysics situations, which will require developments of memory-efficient architectures, parallel computing and domain decomposition methods. Another important future direction is the development of the real-time deployment capabilities, specifically in edge computing environment. The hybrid architecture already shows dramatic increases in computational speeds, and it can be a good candidate to be used in time sensitive applications. The framework is optimizable to run on edge devices by incurring less memory overhead and optimizing the inference of the and leveraging hardware accelerators. This would facilitate real time sense and control in applications like smart grids, autonomous systems and environmental sensing.

Lastly, integrating the use of transformer-based neural operators opens a chance to enhance the learning aspect of the framework further. Transformer architectures have been remarkably successful in long-range dependence capture and complex patterns of high-dimensional data. By embedding operators indicating transformers into the hybrid framework, it may be possible to boost its capacity in modeling complex multiscale interactions, generalized training across various boundary conditions, and training instability. This direction is not only in line with the recent developments in scientific machine learning, but can also greatly increase the performance of the proposed approach. All these future directions should work towards converting the present structure into a more autonomous, scalable and high-performance structure that can deal with more complex nonlinear multiscale problems in real-world scientific and engineering problems.

11. CONCLUSION

The suggested adaptive hybrid numerical-AI architecture offers an efficient and scalable approach to the problem of solving nonlinear

multiscale PDEs based on a seamless combination of physics-based numerical solvers with data-driven neural operators, using an error-driven adaptive process. The outcomes reveal that the framework shows a high predictive accuracy and good physical consistency as illustrated by large decreases in approximation error and PDE residual in several benchmark problems. The approach of integrating the predictability of FEM with the flexibility of neural operators reveals itself as the most successful in terms of the ability to reproduce small-scale nonlinear dynamics compared to simple numerical and AI-based strategies. Moreover, the adaptive refinement approach will allow efficient distribution of computational resources resulting in significant performance gains in runtime and memory consumption without negatively impacting the solution fidelity. In general, the suggested algorithm offers a powerful and computationally efficient strategy to next-generation scientific computing, which has a high potential to be practically implemented in complex multiscale problems in various fields.

REFERENCES

1. Jagtap, A. D., Mao, Z., Adams, N., &Karniadakis, G. E. (2022). Physics-informed neural networks for inverse problems in supersonic flows. *Journal of Computational Physics*, *466*, 111402.
2. Karniadakis, G. E., Kevrekidis, I. G., Lu, L., Perdikaris, P., Wang, S., & Yang, L. (2021). Physics-informed machine learning. *Nature Reviews Physics*, *3*(6), 422-440.
3. Li, Z. (2021). Neural operator: Learning maps between function spaces. In *2021 Fall Western Sectional Meeting*. AMS.
4. Li, Z., Kovachki, N., Azizzadenesheli, K., Liu, B., Bhattacharya, K., Stuart, A., &Anandkumar, A. (2020). Fourier neural operator for parametric partial differential equations. *arXiv preprint arXiv:2010.08895*.
5. Lu, L., Jin, P., Pang, G., Zhang, Z., &Karniadakis, G. E. (2021). Learning nonlinear operators via DeepONet based on the universal approximation theorem of operators. *Nature machine intelligence*, *3*(3), 218-229.
6. Lu, L., Meng, X., Mao, Z., &Karniadakis, G. E. (2021). DeepXDE: A deep learning library for solving differential equations. *SIAM review*, *63*(1), 208-228.
7. Luo, K., Zhao, J., Wang, Y., Li, J., Wen, J., Liang, J., & Liao, S. (2025). Physics-informed neural networks for PDE problems: A comprehensive review. *Artificial Intelligence Review*, *58*(10), 323.
8. Raissi, M., Perdikaris, P., &Karniadakis, G. E. (2019). Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations. *Journal of Computational physics*, *378*, 686-707.
9. Shukla, K., Xu, M., Trask, N., &Karniadakis, G. E. (2022). Scalable algorithms for physics-informed neural and graph networks. *Data-Centric Engineering*, *3*, e24.
10. Sobh, N., Gladstone, R. J., &Meidani, H. (2025). Pinn-fem: A hybrid approach for enforcing dirichlet boundary conditions in physics-informed neural networks. *arXiv preprint arXiv:2501.07765*.
11. Wang, S., Teng, Y., &Perdikaris, P. (2021). Understanding and mitigating gradient flow pathologies in physics-informed neural networks. *SIAM Journal on Scientific Computing*, *43*(5), A3055-A3081.
12. Wang, W., Hakimzadeh, M., Ruan, H., &Goswami, S. (2025). Accelerating Multiscale Modeling with Hybrid Solvers: Coupling FEM and Neural Operators with Domain Decomposition. *arXiv e-prints*, arXiv-2504.
13. Yang, L., Meng, X., &Karniadakis, G. E. (2021). B-PINNs: Bayesian physics-informed neural networks for forward and inverse PDE problems with noisy data. *Journal of Computational Physics*, *425*, 109913.
14. Zhang, Z., Wang, Q., Zhang, Y., Shen, T., & Zhang, W. (2025). Physics-informed neural networks with hybrid Kolmogorov-Arnold network and augmented Lagrangian function for solving partial differential equations. *Scientific Reports*, *15*(1), 10523.